

# **Webasto Stand Solo**

The Webasto Stand Solo is the ideal complement to your Webasto charging station





The Webasto Stand Solo is designed for mounting a single Webasto charging station and impresses with these benefits:

- Corrosion-resistant due to additional electrocoating and powder coating of the steel stand
- Safe operation thanks to earthed connection
- Easy installation due to separate cover
- Mountable on a concrete foundation
- Scope of delivery: stand, screw kit, cover, operating instructions

Technial specifications	
Variant	Webasto Stand Solo
	(Mounting of one charging station)
Dimensions without adapter plate (W x H x D) (mm)	250 x 1497 x 120
Dimensions with adapter plate	300 x 1505 x 190
(W x H x D) (mm)	
Weight (kg)	19
Corrosion Protection	IEC 60068-2-52 severity 2
Material	Steel
Colour	Pillar: RAL 9007
	Cover: Black RAL 9017
Compatible with the following	Webasto Pure, Webasto Next,
charging stations	Webasto Live

The Krinner earth screw makes it even easier to install the stand without earth and concrete work.

The adapter plate connects the Krinner earth screw to the Webasto Stand Solo.

Technial specifications	
Dimensions (W x H x D) (mm)	300 x 6 x 190
Weight (kg)	2,5
Corrosion Protection	By hot-dip galvanizing in accordance with DIN EN 1461 and DIN EN ISO 14731,
	Part 1, 2
Material	Steel
Required fixing material	Krinner earth screw
	KSF M 76 x 1300 - M16



# **Webasto Stand Duo**

The Webasto Stand Duo is the ideal complement to your Webasto charging stations





- Corrosion-resistant due to additional electrocoating and powder coating of the steel stand
- Safe operation thanks to earthed connection
- Easy installation due to separate cover
- Mountable on a concrete foundation
- Scope of delivery: stand, screw kit, cover, operating instructions

Technial specifications	
Variant	Webasto Stand Duo
	(Mounting of two charging stations)
Dimensions without adapter plate	250 x 1497 x 120
(W x H x D) (mm)	
Dimensions with adapter plate	300 x 1505 x 190
(W x H x D) (mm)	
Weight (kg)	19
Corrosion Protection	IEC 60068-2-52 severity 2
Material	Steel
Colour	Pillar: RAL 9007
	Cover: Black RAL 9017
Compatible with the following	Webasto Pure, Webasto Next,
charging stations	Webasto Live

The Krinner earth screw makes it even easier to install the stand without earth and concrete work.

The adapter plate connects the Krinner earth screw to the Webasto Stand Duo.

Dimensions (W x H x D) (mm)	300 x 6 x 190
Weight (kg)	2,5
Corrosion Protection	By hot-dip galvanizing in accordance with
	DIN EN 1461 and DIN EN ISO 14731,
	Part 1, 2
Material	Steel
Required fixing material	Krinner earth screw
	KSF M 76 x 1300 - M16



# **Webasto Stand Slim Solo**



The Webasto Stand Slim is designed for mounting a single Webasto Charging station. Thanks to its simplicity, it is the perfect solution for domestic applications.

### Key facts at a glance:

- Corrosion-resistant due to additional electrocoating and powder coating of the steel stand
- Safe operation thanks to earthed connection
- Easy Installation due to separate cover
- Suitable for all Webasto wallboxes
- Mountable on a concrete foundation
- Scope of delivery: stand, screw set, cover, installation instructions

Technical specifications	
Variants	Webasto Stand Slim Solo
	(Mounting of one charging station)
Dimensions including mounting plate (W × H × D) (mm)	260 x 1500 x 150
Weight (kg)	20
Finish	2 layer coating
	(Electrophoretic and powder)
Corrosion resistance	ISO 9227 NSS
according salt spray test	with test duration 240 hours
Material	Steel
Colour	Signal Black: RAL 9004
Compatible with the following	Webasto Pure, Webasto Next,
charging stations	Webasto Unite, Webasto Live



# Webasto Stand Slim Duo



The Webasto Stand Slim is designed for mounting two Webasto charging stations. Thanks to its simplicity, it is the perfect solution for domestic applications.

## Key facts at a glance:

- Corrosion-resistant due to additional electrocoating and powder coating of the steel stand
- Safe operation thanks to earthed connection
- Easy Installation due to separate cover
- Suitable for all Webasto wallboxes
- Mountable on a concrete foundation
- Scope of delivery: stand, screw set, cover, installation instructions

Technical specifications	
Variants	Webasto Stand Slim Duo
	(Mounting of two charging stations)
Dimensions including mounting plate (W × H × D) (mm)	260 x 1500 x 150
Weight (kg)	20
Finish	2 layer coating
	(Electrophoretic and powder)
Corrosion resistance	ISO 9227 NSS
according salt spray test	with test duration 240 hours
Material	Steel
Colour	Signal Black: RAL 9004
Compatible with the following	Webasto Pure, Webasto Next,
charging stations	Webasto Unite, Webasto Live